



**U2-Mobile S Specifications**

Display	3.5" Color LCD with LED backlight
LED Indicators	Alarm, Ink low, Print, Run, Remote on/off
Input Device	Pocket-sized IR remote keypad
Print Engine Technology	Thermal Inkjet
Available Languages	English, Chinese (Traditional), Chinese (Simplified), Japanese, Russian, Korean, German, Portuguese, Spanish, French, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian Latin, Serbian Cyrillic, Bulgarian, Polish, Vietnam
Max. Printing Resolution	400(h) x 600(v) dpi Print quality is dependent on resolution and speed"
Max. Print Distance	Recommended 6mm from nozzle to surface
Message Height	Up to 12.7mm (0.5") Selectable font size: 1.0mm, 1.4mm, 1.8mm, 2.7mm, 3.6mm, 4.5mm, 5.0mm, 5.5mm, 6.4mm, 8mm, 10mm, 11mm, 12.7mm"
Print Capabilities	Text, String, Logo, Shift, Counter, DateTime, Expiration Date, Barcode
Barcodes	Code-128, ITF-14(SCC-14), NVE(SSCC-18), EAN-128, PDF417, Data Matrix, QR Code, DUN-14, GS1 Datamatrix, GS1 DataBar, GS1 DataBar EXP, GS1 QR CODE, UPCA, UPCE, EAN-13, EAN-14, EAN-8, Codabar, Aztec Code, INTER25, CODEBAR, Code-39
Input/Output	RS-485, RS-232, USB, Wi-Fi
Message Storage Capacity	Store up to 999 messages
Operating Temperature	5°C - 40°C (41°F - 104°F)
Encoder	Embedded (400DPI)
Dimensions	219 mm (L) x136.9 mm (W) x 143.5 mm (H)
Weight	1.13kgs (2.5 lbs) excluding cartridge
Standard Accessories	Battery, battery charger with adapter, USB disk, remote control
Optional Accessories	Wi-Fi dongle, RS-485 to USB converter, Clock stabilizer
PC software	Message Pro II, Net Commander
Printer Control Protoco	ANSER U2 Net Protoco

**Long Lasting Battery**

Rated Capacity	1,840 mAh	Dimensions	100.3(L)x56.3 (W)x21 (H)mm
Standard Voltage	11.1V	Weight	150g (0.33 lbs)
Charging Voltage ( Max )	12.6V	Cycle Life	More than 300 cycles
Charging Hours ( Max )	2 hours	Continuous Printing Hours	4 hours
Operating Temperature	Charge: 0°C - 45°C (32°F - 113°F) Discharge: -20°C-60°C (-4°F-140°F)	Power Adapter of Battery Charger	12.6V 2A
		Stand-by Time	4.5 hours

